

Channels	16CH
IP Video Input	16-ch
Two-way Audio	1-ch RCA(2.0Vp-p, 1k Ω)
VGA Output	1-ch, resolution: 1920×1080P/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
CVBS Output	N/A
HDMI Output	4K HDMI & 1080P VGA
Recording Resolution	5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Audio Output	1-ch RCA(Linear, 1k Ω)
Playback Resolution	5MP / 3MP / 1080P / UXGA / 720P / 4CIF / VGA / DCIF / 2CIF / CIF / QCIF
Synchronous Playback	8-ch
Interface Type	2 SATA Interfaces
Capacity	Up to 4TB capacity for each disk
e-SATA Interface	N/A
Network Interface	1 RJ45 10M/100M/1000M adaptive Ethernet Interface, 4 independent 100Mbps PoE Ethernet interfaces
PoE	16-Port PoE
USB Interface	2 USB 2.0 Interfaces
Serial Interface	1 RS-485 interface (Reserved)
Alarm Input	N/A
Alarm Output	N/A
Power Supply	100~240VAC, 47~63Hz, 3A
Consumption	≤ 15 W (without hard disk)
Working Temperature	-10 °C ~ +55 °C
Working Humidity	10%~90%
Chassis	19-inch rack-mounted 1U chassis
Dimensions	445 × 290 × 45mm (W x D x H)
Weight	≤ 2 Kg (without hard disk)