

<b>Image Sensor</b>	1/1.7" Progressive Scan CMOS
<b>Min. Illumination</b>	0.009 Lux @ (F1.2, AGC ON), 0.012Lux @ (F1.4, AGC ON), 0 Lux with IR
<b>Shutter Time</b>	1s ~ 1/100,000s
<b>Slow Shutter</b>	Support
<b>Lens</b>	2.8~12mm @ F1.4, 96.0°~32.6°
<b>Lens Mount</b>	Φ14
<b>Auto-iris</b>	DC drive
<b>Day &amp; Night</b>	IR Cut Filter with auto switch
<b>Wide Dynamic Range</b>	True WDR
<b>Video Compression</b>	H.264+/H.264/ MJPEG
<b>H.264 Type</b>	Baseline Profile / Main Profile / High Profile
<b>Video Bit Rate</b>	32 Kbps – 16 Mbps
<b>Audio compression rate</b>	G.711/G.722.1/G.726/MP2L2
<b>Audio Bit Rate</b>	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)
<b>Max.Resolution</b>	4096 × 2160
<b>Frame rate</b>	50Hz: 22fps (4096 × 2160), 25fps (3840 × 2160, 1920 × 1080, 1280 × 720) 60Hz: 22fps (4096 × 2160), 24fps (3840 × 2160), 30fps(1920 × 1080, 1280 × 720)
<b>Third Stream</b>	Independent with Main Stream and Sub Stream, up to 50/60Hz: 10fps(1280 × 720)
<b>Image Enhancement</b>	BLC/3D DNR/ROI/Defog
<b>Image Setting</b>	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
<b>Regional Cropping</b>	Support
<b>Distortion Correction</b>	Support
<b>Day/Night Switch</b>	Auto/Schedule/Triggered by Alarm In
<b>Picture Overlay</b>	LOGO picture can be overlaid on video with 128x128 24bit bmp format
<b>Network Storage</b>	NAS (Support NFS,SMB/CIFS), ANR
<b>Alarm Trigger</b>	Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage exception
<b>Protocols</b>	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
<b>Secutity</b>	User Authentication, Watermark, IP address filtering, Anonymous access
<b>Standard</b>	ONVIF(PROFILE S,PROFILE G),PSIA,CGI,ISAPI

<b>Audio(-S)</b>	1-ch audio in( Mic in/Line in)/out interface
<b>Communication Interface</b>	1 RJ45 10M/100M/1000M Ethernet port, 1 RS-485 interface
<b>Alarm(-S)</b>	1 input, 1 output (up to DC24V 1A or AC110V 500mA )
<b>Video Output(-S)</b>	1Vp-p composite output (75 $\Omega$ /BNC)
<b>On-board storage</b>	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
<b>Reset Button</b>	Yes
<b>Environmental Noise Filtering</b>	Support
<b>Audio I/O</b>	Support dual audio track, stereo
<b>Audio Sampling Rate</b>	16kHz / 32kHz / 44.1kHz / 48kHz
<b>Behavior Analysis</b>	Line crossing detection, Intrusion detection, Region entrance, Region exiting, Unattended baggage, Object removal
<b>Line Crossing Detection</b>	Cross a pre-defined virtual line
<b>Intrusion Detection</b>	Enter and loiter in a pre-defined virtual region
<b>Exception Detection</b>	No
<b>Region Entrance</b>	Enter a pre-defined virtual region from the outside place
<b>Region Exiting</b>	Exit from a pre-defined virtual region
<b>Unattended Baggage</b>	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
<b>Object Removal</b>	Objects removed from the pre-defined region, such as the exhibits on display.
<b>Recognition</b>	Face detection recognition
<b>Statistics</b>	Object Counting (Entrance and Exit object number is accounted and showed on screen in real time)
<b>Protection Level</b>	IP66
<b>Operating Conditions</b>	-30°C – 60 °C (-22 °F – 140 °F), Humidity 95% or less (non-condensing); -H: -40°C – 60 °C
<b>Power Supply</b>	24V AC $\pm$ 10%, 12 V DC $\pm$ 10%, PoE (802.3af); -H: 24V AC $\pm$ 10%, 12 V DC $\pm$ 10%, PoE (802.3at);
<b>IR Range</b>	Up to 40m
<b>Power Consumption</b>	Max. 12 W; -H: 17W
<b>Dimension</b>	$\Phi$ 164.9×127 mm ( $\Phi$ 6.49" × 5")
<b>Weight</b>	2100 g ( 4.63 lbs)