

Video Compression	H.264
Analog and HD-TVI Video Input	4-ch, BNC interface (1.0Vp-p, 75 Ω)
Audio Compression	G.711u
Audio Input	4-ch
Audio Input Interface	RCA (2.0 Vp-p, 1 k Ω)
Two-Way Audio	1-ch (Audio In)
VGA Output	1-ch, resolution: 1920×1080P/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
HDMI Output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Recording Resolution	Main stream: 1080P / 720P / VGA / WD1 / 4CIF / CIF; Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame Rate	1/16 fps ~ Real time frame rate
Video Bit Rate	32 Kbps-10 Mbps
Stream Type	Video/Video&Audio
Audio Output	2-ch RCA(Linear, 1k Ω)
Audio Bit Rate	64kbps
Dual Stream	Support
Playback Resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Synchronous Playback	16-ch
Interface Type	4 SATA Interfaces
Capacity	Up to 4TB capacity for each disk
Network Interface	1 RJ45 10M/100M/1000M adaptive Ethernet Interface
USB Interface	3 USB2.0 interfaces
Serial Interface	1RS-485 interface, 1 RS-232 interface, 1 RS-485 keyboard interface
Power Supply	100 ~ 240VAC, 47 ~ 63HZ
Consumption	≤ 55W
Working Temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working Humidity	10% ~ 90%
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions	445 × 390 × 70 mm (17.5 × 15.3 × 2.7 inch)
Weight	≤5Kg (11.0lb)